



# L.I.R. PAINT KIT

## KIT FOR FIELD PAINTING

### L.I.R. FIBERGLASS MASTS

**Paint:** PSX 700 Siloxane High Gloss Paint    Color: 12197 Fed STD 595

**PSX® Advantage:** PSX @700 is the world's first weather-able epoxy it embodies the properties of both a high performance epoxy and an acrylic polyurethane in one coat. This multi-purpose coating offers "breakthrough" weather resistance and corrosion control.

**Mix Ratio:** 2 part mixture - 4 parts resin to 1 part cure

**Pot Life:** 90°F ~ 1.5 hrs; 70°F ~ 4 hrs; 50°F ~ 6.5 hrs

**Application Temperature:** Surface temperatures must be at least 5°F (3°C) above dew point to prevent condensation during application and initial dry through. Relative humidity lower than 40% will extend dry times.

**Coverage:** 289 sq ft (brushing) @ 5 mils thick

Brush - Natural bristle. Maintain wet edge.

Roller - Use industrial roller. Level any air bubbles with bristle brush.

**LIR Mast:** = 1.6 sq ft per foot in length. Ex: 10 ft mast = 16 sq ft.

**Preparation:** We Recommend PREP® 88 water based cleaner, excellent for chalked surfaces, no roughening aged painted surfaces, contains no solvents, biodegradable and dramatically improves aged recoatability.

**PAINT KIT CAN NOT BE SHIPPED BY AIR**

**THIS KIT IS FOR FRANGIBLE MASTS ~ COLOR: SAFETY ORANGE  
FOR NON-FRANGIBLE MASTS ~ COLOR MUST BE: WHITE**

**JAQUITH INDUSTRIES INC**

**600 East Brighton Ave**

**PO Box 780**

**Syracuse, NY 13205 USA**

Phone: 315-478-5700

Fax: 315-478-5707

Web site: [www.jaquith.com](http://www.jaquith.com)

Email: [sales@jaquith.com](mailto:sales@jaquith.com)

P/N 90915003 1 gallon 2 part kit orange

90915004 1 gallon 2 part kit white

90915005 1 gallon PREP® 88

Shipping Weight: 15 lbs per gallon

Contact Jaquith Sales for other colors